

Supplier Information:
Santa Fe Jewelry Supply
1513 Fifth Street Santa Fe, NM 87505

EMERGENCY PHONE.....: 800-255-3924
PREPARATION/REVISION DATE: 03/10/99

342202

TRADE NAME/SYNONYMS...: ANTIQUE GREEN 2 OZ FLAM LIQ
CHEMICAL NAME/SYNONYMS:
CHEMICAL FAMILY.....:
FORMULA.....:
PRODUCT CODE.....: 43.0131

***** HAZARDOUS INGREDIENTS *****

DOES PRODUCT CONTAIN HAZARDOUS INGREDIENTS? (Y,N,N/A,N/I) : Y
CHEMICAL/Common Name CAS-Number PEL-CSHA TLV-ACGIH
PETROLEUM DISTILLATE 64742-89-0 >1 300PPM 300PPM
MINERAL SPIRITS 64742-88-7 >1 100PPM 100PPM
PETROLEUM DISTILLATE 6052-41-3 >1 100PPM 100PPM

DOES PRODUCT CONTAIN CARCINOGENS (NTP, IARC, OR OSHA)? (Y,N,N/A,N/I): N

***** HEALTH HAZARD DATA *****

HEALTH EFFECTS (ACUTE AND CHRONIC)
HARMFUL IF INHALED, MAY AFFECT BRAIN OR NERVOUS SYSTEM, CAUSING DIZZINESS, HEADACHE OR NAUSEA, CAUSES NOSE, THROAT, EYE AND SKIN IRRITATION. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVER-EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. SIGNS AND SYMPTOMS OF EXPOSURE: BREATHING DIFFICULTY, LIGHT HEADEDNESS, CRYSSNESS OF RESPIRATORY TRACT.

PRIMARY ROUTES OF ENTRY
EYES, INHALATION, INGESTION AND SKIN
INHALATION MAY CAUSE DIZZINESS, LOSS OF BALANCE AND COORDINATION, UNCONSCIOUSNESS, RESPIRATORY FAILURE AND DEATH.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
ANY MEDICAL CONDITION, ALLERGY, SENSITIZATION WHICH MAY BECOME WORSE UPON EXPOSURE TO THE PRODUCT.

EMERGENCY FIRST AID PROCEDURES
EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. TAKE TO PHYSICIAN FOR TREATMENT.
INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING. CONSULT A PHYSICIAN.
INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY.
ON SKIN: WASH AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT PHYSICIAN.

SIGNS OF RESPIRATORY TRACT IRRITATION: BREATHING DIFFICULTY, LIGHT HEADEDNESS, CRYSSNESS OF RESPIRATORY TRACT.

***** CHEMICAL DATA *****

BOILING POINT(F)... 230F SPECIFIC GRAVITY(WATER=1)..... 0.95
VAPOR PRESSURE(MMHG) 3.5MM PERCENT VOLATILE BY VOLUME(%)..... N/A
VAPOR DENSITY(AIR=1) >1.0 EVAP RATE(BUTYL ACETATE =1) >1.0

SOLUBILITY IN WATER.. NEGLIGIBLE

APPEARANCE AND COLOR INFORMATION
COLORED LIQUID , MILD ODOR

***** PHYSICAL HAZARD DATA *****

FLASH POINT (METHOD USED) 70F FLAMMABLE LIMITS-LFL= 0.7 UEL= 6.0

EXTINGUISHING MEDIA
WATER SPRAY, ALCOHOL FOAM, DRY CHEMICAL,FOAM, CO2, OR ANY CLASS B EXTINGUISHING AGENT.

SPECIAL FIRE FIGHTING PROCEDURES
WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIRE FIGHTING IN CONFINED SPACE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DO NOT TAKE INTERNALLY. AVOID BREATHING OF VAPOR, FUMES OR DUST. ^{PAGE} KEEP OUT OF ³
REACH OF CHILDREN. AVOID PROLONGED CONTACT WITH SKIN. DO NOT GET IN EYES.
FOLLOW ALL LABEL DIRECTIONS.

OTHER COMMENTS